

SCHUTZHANDSCHUHE
Kategorie II

Benutzerinformation



Benutzerinformation
Schutzhandschuhe gegen mittlere Risiken / Kategorie II



Das Produkt entspricht der Verordnung EU 2016/425. Der REACH Verordnung 1907/2006 nach Annex XVII. Baumusterprüfung durchgeführt durch 0075 CTC Groupe, 4, Rue Hermann Frenkel, 69367 Lyon, Frankreich.

EN388:2016



ABCDEP

A: Abriebfestigkeit Level 0 bis 4
B: Schnittfestigkeit Level 0 bis 5
C: Weiterreißfestigkeit Level 0 bis 4
D: Durchstichfestigkeit Level 0 bis 4
E: Schnittfestigkeit ISO 13997 Level A bis F
P: Schutz gegen Stoß (optional)



Produktionsdatum Jahr/Monat JJJJ/MM

Diese Benutzerinformation ist mit der Produktinformation, die der Verpackung beigelegt ist, zu verwenden.

Lagerung/Verfallzeit:

Handschuhe in Originalverpackung kühl 5-30°C und trocken ohne zusätzliche Gewichtsbelastung lagern und insbesondere vor direktem Sonnenlicht schützen. Nicht in der Nähe von Ozonquellen (z. B. Laserdrucker, -kopierer etc.) lagern. Schutzhandschuhe aus Leder haben eine Verfallzeit von max. 3 Jahren ab Produktionsdatum. Die tatsächliche Verfallzeit im Einsatz kann nicht pauschal angegeben werden, da sie abhängig ist von den Rahmenbedingungen bei der Anwendung. Es ist in jedem Fall eine individuelle Risikobeurteilung im Einzelfall vorzunehmen. Die Angabe des Produktionsdatums erfolgt im Format Jahr/Monat JJJJ/MM.

Gebrauch:

Diese Handschuhe sind zum Schutz vor mittleren Risiken gedacht. Schutzhandschuhe immer nur für den vorgesehenen Einsatzbereich und in der richtigen Größe verwenden. Es ist eine Überprüfung/Risikobeurteilung vorzunehmen, um sicherzustellen, dass die Handschuhe für die vorgesehene Verwendung geeignet sind, da die Bedingungen am Arbeitsplatz in Abhängigkeit von Temperatur, Abrieb und Degradation von denen der Typprüfung abweichen können. Falls ein Schutz vor Stoß angegeben ist, gilt der Schutzbereich nicht für die Finger. Beim Auftreten von Abstumpfung während der Schnittfestigkeitsprüfung Coupe Test, sind die Ergebnisse der Schnittfestigkeitsprüfung nach EN 388:2016 nur als Hinweise zu verstehen, wohingegen die Schnittfestigkeitsprüfung nach EN 388:2016 TDM Referenzergebnisse bezüglich der Leistung liefert. Die Handschuhe sind nicht schnitthemmend oder schnittbeständig. Verwenden Sie diese Handschuhe nicht zum Schutz vor gezackten Kanten oder Schneiden. Im Bereich rotierender Maschinenteile (Sägeblätter, Bohrer etc.) keine Handschuhe tragen. Die Handschuhe erfüllen die Vorgaben der Durchstichfestigkeitsprüfung (spitze Gegenstände) schützen jedoch nicht vor Stichen mit Injektionsnadeln! Vor der Anwendung sind die Handschuhe auf jegliche Fehler wie Löcher, Risse oder andere Mängel, wie z. B. Verfärbung zu überprüfen. Schadhafte Handschuhe dürfen auf keinen Fall verwendet werden. Tests wurden an der Handfläche durchgeführt. Vorhandene Größen 7 bis 12 abhängig vom Artikel. Größen für besonderen Zweck geeignet.

Reinigung/Desinfektion:

Eine Reinigung/Desinfektion ist für diese Handschuhe nicht vorgesehen und erfolgt in eigener Verantwortung.

Entsorgung:

Gebrauchte Handschuhe sind entsprechend der Entsorgungsvorschriften der Verschmutzung und der Vorschriften der örtlichen Behörde zu entsorgen. Unbenutzte Handschuhe können mit dem Hausmüll entsorgt werden.

Warnhinweise/Allergiker Hinweise:

Im Bereich rotierender Maschinenteile (Sägeblätter, Bohrer etc.) keine Handschuhe tragen. Es besteht die Gefahr, mitgerissen zu werden! Lederhandschuhe können allergische Reaktionen hervorrufen und einige Handschuhmodelle enthalten Naturlatex und können bei Allergikern allergische Reaktionen hervorrufen. Bei Hautreizungen oder allergischen Reaktionen holen Sie bitte umgehend ärztlichen Rat ein.

Weitere Informationen:

Über die Leistungen des Handschuhs oder der Inhaltsstoffe können Informationen beim Hersteller angefordert werden.

Diese Anwenderinformation wurde dem Polybeutel (12 Paar) beigelegt. Bei paarweisem Verkauf muss Diese vervielfältigt und paarweise ausgehändigt werden!

Konformitätserklärung: siehe www.staffl-arbeitsschutz.at

POLIER 0102

J.STAFFL®

5 Finger Handschuh, ca. 1,1mm starkes Schweinsvollleder, Fingerspitzen, Knöchelschutz und Daumen aus Schweinsvollleder, Handrücken Baumwolle. Gummizug am Handrücken, Handfläche mit Baumwolle gefüttert, Verstärkte Sicherheitsstulpe, Kategorie 2, Leder gelb, Stoff grün, mechanischer Schutzhandschuh für Arbeiten in trockenem Umfeld. Geringer thermischer Schutz. Anwendungsbereiche: Bau, Transport und Logistik, Land- und Forstwirtschaft, Gartenarbeit.



EN 420:2003+A1:2009



3121X

X = nicht getestet / nicht anwendbar

MATERIALBESCHREIBUNG Leder

Schweinsleder

MATERIALBESCHREIBUNG Stoff

Baumwolle

Größen 9, 10.5, 11

Fingerfertigkeit 5

EG Baumusterprüfbescheinigung

Notified Body 0075 CTC Groupe, 4, Rue Hermann Frenkel, 69367 Lyon, France

Kartoninhalt 120 Paar (10x 12 Paar)

Größen / Farbcode am Bund

9	10	11
LARGE	X-LARGE	XX-LARGE
-	-	-

PROTECTIVE GLOVES

Category II

Instruction for Use



Instruction for Use
Protective Gloves against medium Risks / Category II



The products is in compliance with the EU Regulation 2016/425. REACH regulation EU 1907/2006 according to Annex XVII.
Type examination carried out by 0075 CTC Groupe, 4, Rue Hermann Frenkel, 69367 Lyon, France.

EN388:2016



ABCDEP

A: Abrasion resistance levels 0 to 4
B: Blade cut resistance levels 0 to 5
C: Tear resistance levels 0 to 4
D: Puncture resistance levels 0 to 4
E: Blade cut resistance ISO 13997 level A - F
P: Protection against impacts (optional)



Production date Year/Month YYYY/MM

This user information must be used in conjunction with specific product information that is enclosed with the packaging.

Instruction for Use

Protective Gloves against medium Risks / Category II

Storage/expiry date:

Store gloves in the original packaging in a cool (5-30°C) dry place and protect, particularly against direct sunlight. Do not store in the vicinity of ozone sources (e.g. laser printers, copiers etc.). Protective gloves made of Leather have a shelf-life of no more than 3 years from the production date. The actual shelf-life during use cannot be specified at a general level because it depends on the conditions of use. A distinct risk assessment must be performed for each individual case.

The production date is stated in the format year/month yyyy/mm.

Use:

These gloves are intended for protection against medium risks. Only use protective gloves for their intended purpose and in the correct size. A check/risk assessment must be carried out to ensure that the gloves are suitable for the intended use because the conditions in the place of work in relation to temperature, abrasion and degradation may vary from those of the type approval test. If impact protection is stated, the protection area does not apply to the fingers. When blunting occurs during the blade cut resistance test, the EN388:2016 Coupe cut resistance test results should be considered for guidance only, whereas the EN388:2016 TDM blade cut test provides reference results in respect of performance. These gloves resist cut but are not cut proof. Do not subject to high speed or serrated blades. Gloves meeting the requirement for resistance to puncture may not be suitable for protection against sharply pointed objects such as hypodermic needles. Before use, the gloves should be checked for any defects such as holes, cracks or other defects, e.g. discoloration. Never use damaged gloves. Test is taken from the palm area of the glove. Available sizes from 7 to 12. Depending on the article.

Fit for special purpose.

Cleaning/disinfection:

It is not intended that these gloves should be cleaned/disinfected and if doing so, the user bears full responsibility.

Disposal:

Dispose of used gloves dependent on the soiling level and in accordance with the applicable disposal regulations and local authority regulations. Unused gloves can be disposed of with domestic waste.

Warnings / allergy notes:

Do not wear gloves in the vicinity of rotating machine parts (saw blades, drills etc.). Risk of entanglement! Leather gloves may cause allergic reactions, some gloves contain natural latex and may cause allergic reactions in people with allergies. Seek immediately medical advice in case of skin irritations or allergic reactions.

Further information:

For further information about the gloves or their contents please contact the manufacturer.

Further information:

For further information about the gloves or their contents please contact the manufacturer.

This instruction for use (IFU) is packed into a bundle (12 pairs). If bundle is broken for single pair sale, the IFU has to be copied and added to single pair!

Declaration of conformity: see www.staffl-arbeitsschutz.at

PRODUCT SPECIFIC INFORMATION

POLIER 0102

J.STAFL®

5 Finger glove, 1.1mm thick piggrain leather on palm, fingertips, thumb and knuckle strap made of piggrain leather, back made of cotton textile, pasted safety cuff, palm cotton lined, Category 2, yellow piggrain, green fabric, mechanical work gloves for work under dry environments.

Applications: Gardening, construction, transport and logistics, agriculture and forestry.



EN 420:2003+A1:2009



3121X

X = not tested / not applicable

MATERIAL SPECIFICATION LEATHER

Piggrain

MATERIAL SPECIFICATION LINER

Cotton

SIZE 9, 10.5, 11

DEXTERITY 5

EC TYPE EXAMINATION

Notified Body 0075 CTC Groupe, 4, Rue Hermann Frenkel, 69367 Lyon, France

PACKAGING 120 Pair (10x 12 Pair)

SIZES / Colorcode wrist

9	10	11
LARGE	X-LARGE	XX-LARGE
-	-	-