Benutzerinformation

0075

EN388:2016 + A1:2018

2132X

EN407:2020

X1XXXX

Diese Produkte werden gemäß der europäischen PSA-Verordnung 2016/425 als Persönliche Schutzausrüstung (PSA) eingestuft und entsprechen dieser Verordnung nachweislich durch die harmonisierten europäischen Normen EN ISO 21420:2020 und EN 388:2016+A1:2018.
Benannte Stelle verantwortlich für die Zertifizierung: 0075 CTC, 4 rue Hermann Frenkel, 69367 Lyon - Cedex 07, France.

DRIVER PREMIUM 0801

5 Finger Handschuh, weiches hochwertiges Rindleder, Handfläche und Zeigefinger aus Rindleder, Handrücken aus Rindleder, Kategorie 2, Leder grau, Gummizug am Handrücken, ungefüttert, mechanischer Schutzhandschuh für Arbeiten in trockenen Umfeld. Sehr gute Fingerfertigkeit für Montagearbeiten.
Anwendungsbereiche: Trockenbau, Transport und Logistik, Landwirtschaft, Gartenarbeit, Werkstatt, Instandhaltung.

MATERIALBESCHREIBUNG: Rindvollleder
MATERIALBESCHREIBUNG FUTTER: -
Verfügbare Größen: 8, 9, 10, 11, 12 (auf jedem Handschuh markiert)
Fingerfertigkeit: 5
Kartoninhalt: 120 Paar (10x 12 Paar)

Ergebnisse nach EN388:2016 + A1:2018
A: Abriebfestigkeit Level 2 von 4
B: Schnittfestigkeit Level 1 von 5
C: Weiterreißfestigkeit Level 3 von 4
D: Durchstichfestigkeit Level 2 von 4
E: TDM Schnittfestigkeit ISO 13997 Level X von A bis F
P: Schutz gegen Stoß (optional)

X = dieser Test wurde nicht durchgeführt
0 = der Handschuh liegt unter dem Mindestleistungsniveau für die jeweilige einzelne Gefährdung.

Level	1	2	3	4	5
Abriebfestigkeit (Anzahl der Zyklen)	100	500	2000	8000	-
Schnittfestigkeit (Index)	1.2	2.5	5.0	10.0	20.0
Weiterreißfestigkeit	10	25	50	75	-
Durchstichfestigkeit	20	60	100	150	-

Test	Level A	Level B	Level C	Level D	Level E	Level F
TDM Schnitt-festigkeit (N)	2	5	10	15	22	30

Ergebnisse nach EN407:2020
A: Begrenzte Flammenausbildung Level X von 4
B: Kontakthitze Level 1 von 4 (>= 15 Sek. 100°C)
C: Konvektionshitze Level X von 4
D: Strahlungshitze Level X von 4
E: Kleine Spritzer geschmolzenen Metalls Level X von 4
F: Große Mengen geschmolzenen Metalls Level X von 4
X = nicht getestet
Schutz vor Hitze ohne Flamme

Größenangaben in mm +/- 5mm

Größe	8 / M	9 / L	10 / XL	11 / XXL	12 / XXXL
Handumfang (mm)	210	220	230	240	250
Länge (mm)	240	250	260	270	280

LOT Bestellnummer

Produktionsdatum Jahr/Monat

Haltbarkeitsdatum Jahr/Monat

Vorgesehene Verwendung: Diese Handschuhe sind zum Schutz vor mittleren Risiken gedacht. Schutzhandschuhe immer nur für den vorgesehenen Einsatzbereich und in der richtigen Größe verwenden. Es ist eine Überprüfung/Risikobeurteilung vorzunehmen, um sicherzustellen, dass die Handschuhe für die vorgesehene Verwendung geeignet sind, da die Bedingungen am Arbeitsplatz in Abhängigkeit von Temperatur, Abrieb und Degradation von denen der Typ prüfung abweichen können. Falls ein Schutz vor Stoß angegeben ist, gilt der Schutzbereich nicht für die Finger. Nicht in der Nähe von beweglichen Maschinen verwenden – Gefahr von Verhedderung. Der Handschuh kann bei Nässe seine isolierenden Eigenschaften verlieren. Flammschutz wird nicht beansprucht. Der Handschuh wurde keiner flammhemmenden Behandlung unterzogen. Die Leistungsstufen gelten für den gesamten Handschuh einschließlich aller Schichten.
Lagerung und Transport: Wenn nicht in Gebrauch, das Produkt in einem gut belüfteten Bereich lagern, fern von extremen Temperaturen und Sonnenlicht. Vor Gebrauch auf Beschädigungen oder Mägel prüfen – beschädigte Handschuhe nicht verwenden.
Leistung: Die angegebene Handschuhleistung basiert auf Labordaten und kann aufgrund anderer Einflussfaktoren wie Temperatur, Abrieb oder Abnutzung die tatsächliche Schutzdauer am Arbeitsplatz nicht widerspiegeln. Testergebnisse beziehen sich auf den Handflächenbereich des Handschuhs. Diese Informationen berücksichtigen nicht die tatsächliche Schutzdauer am Arbeitsplatz. Die mechanische Beständigkeit wurde unter Laborbedingungen anhand von Proben aus dem Handflächenbereich geprüft. Die Gesamtklassifikation von Handschuhen mit zwei oder mehr Schichten spiegelt nicht unbedingt die Leistung der äußersten Schicht wider.
An- und Ausziehen: Die Hände vor dem Anziehen der Handschuhe trocknen, die Handschuhe an die Finger, die Handfläche und das Handgelenk anpassen. Handschuhe durch Ziehen am Stulpenbereich ausziehen.
Reinigung/Desinfektion: Mit einem feuchten Tuch abwischen. Eine andere Reinigung/Desinfektion ist für diese Handschuhe nicht vorgesehen und erfolgt in eigener Verantwortung.
Allergiehinweis: Handschuhe aus Leder können allergische Reaktion auslösen. Einige Handschuhmodelle enthalten Naturlatex und können bei Allergikern allergische Reaktionen hervorrufen. Bei Hautreizungen oder allergischen Reaktionen holen Sie bitte umgehend ärztlichen Rat ein.
Entsorgung: Gebrauchte Handschuhe sind entsprechend der Entsorgungsvorschriften der Verschmutzung und der Vorschriften der örtlichen Behörde zu entsorgen. Unbenutzte Handschuhe können mit dem Hausmüll entsorgt werden.
Weitere Informationen: Über die Leistungen des Handschuhs oder der Inhaltsstoffe können Informationen beim Hersteller angefordert werden. Diese Anwenderinformation wurde dem Polybeutel (12 Paar) beigepackt. Bei paarweisem Verkauf muss Diese vervielfältigt und paarweise ausgehändigt werden!

Die EU Konformitätserklärung wird auf der Website https://www.staffl-arbeitsschutz.at/produkte/ angezeigt.

USERINFORMATION

0075

EN388:2016 + A1:2018

2132X

EN407:2020

X1XXXX

These products are classified as Personal Protective Equipment (PPE) according to the European PPE Regulation 2016/425 and have been shown to comply with this regulation through the harmonized European standard(s) EN ISO 21420:2020, EN 388:2016+A1:2018 and EN407:2020.
Notified Body responsible for certification: 0075 CTC, 4 rue Hermann Frenkel, 69367 Lyon - Cedex 07, France.

DRIVER PREMIUM 0801

5-Finger Glove, approximately 1.2mm cowhide leather, palm and index finger made of cowhide leather, back made of cowhide leather, smooth surface, Category 2, grey leather, unlined. A mechanical work gloves all round performance suitable for most construction work and general industrial assembly operations under dry environments.

MATERIAL SPECIFICATION LEATHER: Cowgrain
MATERIAL SPECIFICATION LINER: unlined
Available Sizes: 8, 9, 10, 11, 12 (marked on each glove)
Dexterity: 5
Carton Content: 120 pairs (10 x 12 pairs)

Results according to EN 388:2016 + A1:2018
A: Abrasion resistance Level 2 of 4
B: Blade cut resistance Level 1 of 5
C: Tear resistance Level 3 of 4
D: Puncture resistance Level 2 of 4
E: TDM cut resistance ISO 13997 Level X from A to F
P: Impact protection (optional)

Key:
X = This test was not conducted
0 = The glove does not meet the minimum performance level for the respective hazard.

Level	1	2	3	4	5
Abrasion resistance (Number of cycles)	100	500	2000	8000	-
Blade cut resistance (Index)	1.2	2.5	5.0	10.0	20.0
Tear resistance (N)	10	25	50	75	-
Puncture resistance (N)	20	60	100	150	-

Test	Level A	Level B	Level C	Level D	Level E	Level F
TDM cut resistance (N)	2	5	10	15	22	30

Results according to EN 407:2020
A: Limited flame spread levels X of 4
B: Contact heat Level 1 of 4 (>= 15 sec. 100°C)
C: Convective heat Levels X of 4
D: Radiant heat Level X of 4
E: Small splashes of molten metal Level X of 4
F: Large quantities of molten metal Level X of 4
Protection against heat without flame

Key:
X = This test was not conducted
0 = The glove does not meet the minimum performance level for the respective hazard.

Sizing and measurement in mm +/- 5mm

Hand size	8 / M	9 / L	10 / XL	11 / XXL	12 / XXXL
Hand circumference (mm)	210	220	230	240	250
Hand Length (mm)	240	250	260	270	280

LOT Purchase order number

Production date Year/Month YYYY/MM

Obsolescence date Year/Month YYYY/MM

Intended Use: These gloves are designed for protection against medium risks. Protective gloves should only be used for their intended purpose and in the correct size. A review/risk assessment must be carried out to ensure the gloves are suitable for their intended use, as workplace conditions may differ from those of type testing due to factors such as temperature, abrasion, and degradation. If impact protection is specified, the protection area does not apply to the fingers. Do not use near moving machinery – risk of entanglement. The performance levels and protection apply only to the entire glove. No flame protection is claimed. The glove has not been subjected to any flame-retardant treatment. The performance levels apply to the entire glove, including all layers.
Storage and Transport: When not in use, store the product in a well-ventilated area, away from extreme temperatures and sunlight. Inspect for damage or defects before use – do not use damaged gloves.
Performance: The stated glove performance is based on laboratory data and may not reflect the actual protection duration in the workplace due to factors such as temperature, abrasion, or wear. Test results refer to the palm area of the glove. These details do not account for actual protection duration in the workplace. Mechanical resistance has been tested under laboratory conditions using samples from the palm area. The overall classification of gloves with two or more layers does not necessarily reflect the performance of the outermost layer.
Donning and Doffing: Dry hands before putting on gloves. Adjust gloves to fit the fingers, palm, and wrist. Remove gloves by pulling at the cuff area.
Cleaning/Disinfection: Wipe with a damp cloth. Any other cleaning/disinfection is not intended for these gloves and is carried out at your own risk.
Allergy Warning: Leather gloves may cause allergic reactions. Some glove models contain natural latex and may trigger allergic reactions in sensitive individuals. In case of skin irritation or allergic reactions, seek medical advice immediately. Do not expose to open flame. Flame protection is not claimed. Glove has not undergone any flame-reardant treatment (BDE).
Disposal: Used gloves must be disposed of in accordance with contamination disposal regulations and local authority guidelines. Unused gloves can be disposed of with household waste.
Additional Information: Further information about glove performance or ingredients can be requested from the manufacturer. This user information has been included with the polybag (12 pairs). For single-pair sales, this information must be duplicated and handed out with each pair.

The EU Declaration of Conformity is available on the website: https://www.staffl-arbeitsschutz.at/produkte/